

Torca[®] AccuSeal[®] Exhaust Clamps

with & without sleeve

Featuring reaction block technology, invented by Torca, AccuSeal Exhaust Clamps provide 360° equal distribution of sealing force, prohibiting pipe distortion while completing a tight, durable seal around the joined exhaust components.



Pre-Assembled for Easy Installation

- AccuSeal clamps are easily positioned, securing reliable exhaust slip joints
- Easy to disassemble and service

Works with Thin Gauge, Corrosive-Resistant Materials

Efficient Material Use for Reduced Weight & Assembly Cost





AccuSeal® Exhaust Clamps

AccuSeal exhaust clamps feature reaction block technology, invented by Torca, providing 360° equal distribution of stretching force, prohibiting pipe distortion while completing a tight, durable seal around the joined exhaust components.

- For slotted lap style joint connection
- Hexavalent chrome-free
- High clamp load capability

AccuSeal


For slotted and overlapped exhaust pipe joints.



1-3/4" – 7" (44.5mm – 177.8mm) Diameter range

Competitive Advantages

- Materials: Wide range of materials available



ALUMINUM FINISH ACCUSEAL		STAINLESS FINISH ACCUSEAL		BRIGHT FINISH ACCUSEAL		Nominal Joint Diameter	
Brand PN	Global PN	Brand PN	Global PN	Brand PN	Global PN	inches	mm
A17AF	0366 0050 500	A17SF	0366 0050 499	A17BF	0366 0080 500	1-3/4	44.5
A20AF	0366 0060 564	A20SF	0366 0040 564	A20BF	0366 0000 564	2	50.8
A22AF	0366 0020 627	A22SF	0366 0080 627	A22BF	0366 0060 627	2-1/4	57.2
A25AF	0366 0030 691	A25SF	0366 1200 691	A25BF	0366 0000 691	2-1/2	63.5
A27AF	0366 0020 754	A27SF	0366 0070 754	A27BF	0366 0050 754	2-3/4	69.9
A30AF	0366 0070 818	A30SF	0366 0030 818	A30BF	0366 1200 818	3	76.2
A35AF	0366 0060 949	A35SF	0366 0000 949	A35BF	0366 0020 949	3-1/2	88.9
A40AF	0366 0071 072	A40SF	0366 1241 072	A40BF	0366 1221 072	4	101.6
A45AF	0366 0021 199	A45SF	0366 0001 188	A45BF	0366 0011 199	4-1/2	114.3
A50AF	0366 0061 326	A50SF	0366 1211 326	A50BF	0366 0021 326	5	127.0
A60AF	0366 0041 580	A60SF	0366 0061 580	A60BF	0366 0021 580	6	152.4
A70AF	0366 0021 841	-	-	A70BF	0366 0031 841	7	177.8

AccuSeal with Sleeve


Exhaust clamp with protective sleeve; stainless steel clamp and sleeve.



1-3/4" – 7" (44.5mm – 177.8mm) Diameter range

Competitive Advantages

- Materials: Aluminized steel/409 & 304 stainless steel
- Designed for use with Bellows tube – prevents thin-walled pipe from damage



304 ACCUSEAL W/SLEEVE		Band Material	Sleeve Material	Nominal Joint Diameter	
Brand PN	Global PN			inches	mm
18-0005	0366 0010 673	304 Stainless Steel	304 Stainless Steel	2-1/2	63.5
18-0006	0366 0000 736	304 Stainless Steel	304 Stainless Steel	2-3/4	69.9
18-0007	0366 0010 800	304 Stainless Steel	304 Stainless Steel	3	76.2
18-0008	0366 0010 927	304 Stainless Steel	304 Stainless Steel	3-1/2	88.9
18-0009	0366 0011 054	304 Stainless Steel	304 Stainless Steel	4	101.6
18-0010	0366 0001 308	304 Stainless Steel	304 Stainless Steel	5	127.0

409 ACCUSEAL W/SLEEVE		Band Material	Sleeve Material	Nominal Joint Diameter	
Brand PN	Global PN			inches	mm
18-0011	0366 0000 673	409 Stainless Steel	304 Stainless Steel	2-1/2	63.5
18-0012	0366 0010 736	409 Stainless Steel	304 Stainless Steel	2-3/4	69.9
18-0013	0366 0000 800	409 Stainless Steel	304 Stainless Steel	3	76.2
18-0014	0366 0000 927	409 Stainless Steel	304 Stainless Steel	3-1/2	88.9
18-0015	0366 0001 054	409 Stainless Steel	304 Stainless Steel	4	101.6
18-0016	0366 0011 308	409 Stainless Steel	304 Stainless Steel	5	127.0

NORMA Americas Distribution Services

325 West Silverbell Road, Suite 230 | Lake Orion, MI 48359 USA
 Tel 1.855.NORMA2U | 1.855.667.6228 | Fax 1.855.804.4646 | Email norma2u@normagroup.com | www.normaAmericasDS.com

